


# CABLE MARKERS

1



## APPLICATORS FOR O-TYPE AND Z-TYPE MARKERS

- 6 sizes
- PTFE coating for easy marker application

A range of applicators suitable for either Z – or O-Type™ markers. Made from PTFE

coated steel to provide easy marker application.



## V-TYPE™ MARKERS

- Temperature rating from  $-45^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$  ( $-50^{\circ}\text{F}$  to  $+158^{\circ}\text{F}$ ).
- Resistant to sea water, fuels and oils.
- 4 sizes covering wire diameters from 1.4mm to 16.0mm (0.06 to 0.63 inches)

V-Type™ markers are individual push-on characters used to identify wires and small cables permanently. They are designed with an expanding profile, enabling each marker to accommodate a wide range of wire/cable sizes. V-Type™ markers are a simple, cost-effective solution for many commercial wire identification applications.


The markers are supplied chevron cut and this ensures the legends remain aligned.

Standard V-Type™ markers are yellow or white with black legends and can be supplied as loose pieces packed in boxes, on reels or flat disc reels. Color coded markers are also available.

**SERVICE TEMPERATURE RANGE:**  $-45^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$  ( $-50^{\circ}\text{F}$  to  $+158^{\circ}\text{F}$ ).

**MATERIAL:** Plasticized polyvinyl chloride (PPVC).

**MARKS AVAILABLE:** A-Z, 0-9, +, -, /, phase, earth, blank and full stop.



## PERMARK® MARKERS

- Pre-marked to customer requirements.
- Customer-defined kits for ease of installation.
- Excellent character legibility.
- One-piece, 316 stainless steel construction.
- Variety of fixing methods.
- Mark will endure the lifetime of a Permark® S/S marker.
- Excellent resistance to weather extremes and high levels of UV light.
- Resistant to corrosive marine and industrial atmospheres.
- Excellent resistance to a variety of hydrocarbons, organic chemicals, acids, alkalis and inorganic salts. For resistance to a specific chemical, contact your local Tyco representative.

Tyco Permark® 316 stainless steel markers are recommended for marking in hostile environments. Using state-of-the-art technology and no inks, the marking process produces a permanent, deep surface mark with a darkened character in high contrast to the background. Permark® markers are produced to individual customer requirements on a fast turn-around basis with the flexible and easy-to-use Permark® software that allows electronic or manual data entry. Completed markers are supplied in customer defined kits for ease of installation. We recommend installation with 316 stainless steel cable ties.

**SERVICE TEMPERATURE RANGE:**  $80^{\circ}\text{C}$  to  $+500^{\circ}\text{C}$  ( $112^{\circ}\text{F}$  to  $+932^{\circ}\text{F}$ ).

**MATERIAL:**

Stainless Steel

**PRINTER INFORMATION:**

Pre-printed per customer requirements.

Permark® Speciality Products

# CABLE MARKERS



## G-TYPE™ MARKERS

For Cable dia mm	For Cable size• mm² (BS6004) (BS6231)	Marker size	Packed Box (A)	Order code
1.4 – 2.5	–	G3/10	1000	0719
2.0 – 3.5	1.0 – 2.5	G3/20	1000	0720
3.0 – 6.0	1.5 – 6.0	G4/10	500	0721
5.0 – 9.5	10.0 – 25.0	G6/10	250	0722
8.0 – 12.5	25.0 – 50.0	G6/20	250	0723

\*Application to cables BICC Ref. No. 6491X

### COLOUR OPTIONS

**Yellow body marked black:**  
A-Z, 0-9 and symbols.

### MATERIAL

Modified thermoplastic compound (holgen, silicone and cadmium free).

### SERVICE TEMPERATURE RANGE

–45°C to +70°C.


### FLAMABILITY

LOI 42%, UL94 V-0.  
FTI>350°C.

### CHEMICAL RESISTANCE

**Excellent:** Propan-2-ol, 10% Hydrochloric Acid, 10% Sodium Hydroxide, 10% Detergent, Sea Water, Tap Water. **Good:** Cutting Oils, Gear Oil, Gas Turbine Oil, Methanol, Acetone, Petrol, Diesel, Aeroshell 41, Skydrol, Versilube V50.

## APPLICATORS For 0- and Z-Type Markers



Size	O-Type sizes	Z-Type sizes	Packed	Order code
1	20	7	1	1251
2	25	9	1	1252
3	30	11	1	1253
4	40	13	1	1254
5	–	15	1	1255
6	55	18	1	1256