


CABLE MARKERS

1



APPLICATORS FOR O-TYPE AND Z-TYPE MARKERS

- 6 sizes
- PTFE coating for easy marker application

A range of applicators suitable for either Z – or O-Type™ markers. Made from PTFE

coated steel to provide easy marker application.



V-TYPE™ MARKERS

- Temperature rating from -45°C to $+70^{\circ}\text{C}$ (-50°F to $+158^{\circ}\text{F}$).
- Resistant to sea water, fuels and oils.
- 4 sizes covering wire diameters from 1.4mm to 16.0mm (0.06 to 0.63 inches)

V-Type™ markers are individual push-on characters used to identify wires and small cables permanently. They are designed with an expanding profile, enabling each marker to accommodate a wide range of wire/cable sizes. V-Type™ markers are a simple, cost-effective solution for many commercial wire identification applications.


The markers are supplied chevron cut and this ensures the legends remain aligned.

Standard V-Type™ markers are yellow or white with black legends and can be supplied as loose pieces packed in boxes, on reels or flat disc reels. Color coded markers are also available.

SERVICE TEMPERATURE RANGE: -45°C to $+70^{\circ}\text{C}$ (-50°F to $+158^{\circ}\text{F}$).

MATERIAL: Plasticized polyvinyl chloride (PPVC).

MARKS AVAILABLE: A-Z, 0-9, +, -, /, phase, earth, blank and full stop.



PERMARK® MARKERS

- Pre-marked to customer requirements.
- Customer-defined kits for ease of installation.
- Excellent character legibility.
- One-piece, 316 stainless steel construction.
- Variety of fixing methods.
- Mark will endure the lifetime of a Permark® S/S marker.
- Excellent resistance to weather extremes and high levels of UV light.
- Resistant to corrosive marine and industrial atmospheres.
- Excellent resistance to a variety of hydrocarbons, organic chemicals, acids, alkalis and inorganic salts. For resistance to a specific chemical, contact your local Tyco representative.

Tyco Permark® 316 stainless steel markers are recommended for marking in hostile environments. Using state-of-the-art technology and no inks, the marking process produces a permanent, deep surface mark with a darkened character in high contrast to the background. Permark® markers are produced to individual customer requirements on a fast turn-around basis with the flexible and easy-to-use Permark® software that allows electronic or manual data entry. Completed markers are supplied in customer defined kits for ease of installation. We recommend installation with 316 stainless steel cable ties.

SERVICE TEMPERATURE RANGE: 80°C to $+500^{\circ}\text{C}$ (112°F to $+932^{\circ}\text{F}$).

MATERIAL:


Stainless Steel

PRINTER INFORMATION:

Pre-printed per customer requirements.

Permark® Speciality Products

CABLE MARKERS



PERMARK® MARKERS

Available sizes and formats
Ordering description

Ordering description	Product description	Size (L x H)		Printable area (L x H)	
		mm	inches	mm	inches
PM09512-<# text lines>--<# characters>	Pre-marked 316 S/S marker	95 x 12	3.74 x 0.47	55 x 10	2.16 x 0.40

Options

Fonts	Various available
Lines per marker	One, two or three (Determined by selected font height. Minimum 1 mm / 0.04" spacing between lines.)
Saddle fixings	13 mm L x 2.4 mm H (0.51" L x 0.09" H)
Hole fixings	7 mm (0.28")
Standard colours	Metallic

Font heights	Characters per line	
	Standard	Condensed
2.5 mm (0.10")	30	N/A
3.0 mm (0.12")	25	N/A
4.0 mm (0.16")	20	30
5.0 mm (0.20")	15	25
6.0 mm (0.24")	15	25
8.0 mm (0.31")	10	20
10.0 mm (0.40")	10	15

Available sizes and formats
Ordering description

Ordering description	Product description	Size (L x H)		Printable area (L x H)	
		mm	inches	mm	inches
PM07507-1--<# characters>	Pre-marked 316 S/S marker	75 x 7	2.95 x 0.28	50 x 5	1.6 x 0.20

Options

Fonts	Various available
Lines per marker	One only
Saddle fixings	9.5 mm L x 2.4 mm H (0.37" L x 0.09" H)
Hole fixings	None
Standard colours	Metallic

Font heights	Characters per line	
	Standard	Condensed
4.0 mm	(0.16")	15 25
5.0 mm	(0.20")	10 20

Part numbering system:

